






Complex solutions for Light Rail Vehicles

GHH-BONATRANS is the world leading supplier of wheelset solutions for low-floor applications. From driven wheelset to the independent wheel unit, we design, engineer and manufacture each element of the wheelset system. From development and engineering to production, assembly and maintenance/overhaul, the complete wheelset system is the core of our expertise. We have established long-term partnerships with the major manufacturers of Light Rail Vehicles in order to gain excellent knowledge and provide the best possible expertise and consultancy already in the early stages of product development.




Solutions for all floor levels



Drive and brake between the wheels, but with limited height

Our solution: driven and non-driven wheelsets


Result: Floor level of 550 mm



No drive nor brake between the wheels

Our solution: driven and non-driven wheelsets


Result: Floor level of 450 mm



No drive nor brake between the wheels, independent wheels

Our solution: independent wheels on the axles

Result: Floor level of 350 mm



Running gears with portal frame

Our solution: swivel-mounted independent wheel units, fixed on portal frame

Result: Floor level of 205 mm

Selected customers



















Innovated wheel and axle portfolio




GHH Radsatz GmbH has developed a new Super-Resilient Wheel for 12.5-ton axle loads. The wheel meets all requirements for a Resilient Wheel with nominal diameter down to 600 mm new / 520 mm worn. The design of all components has been enhanced and the rubber elements have been completely reshaped. Excellent strength of the **GHH®ULTRA-S** was verified by applying the German quality standards (FEM analysis and assessment of stresses by application of FKM-quideline).

Next generation of independent wheel axle

The new 12.5t independent wheel axle is based on the proven and reliable **GHH**°*V60* wheel type. Its modern upgrade for high axle loads is based on a one-piece, die-forged portal axle design and a pair of tapered roller bearings, adjusted optimally during assembly.

Resilient wheel product range


Resilient wheels



BONAE-LOCK®M




GHH®V15



GHH®V60


Super-resilient wheels




GHH[®]*ULTRA-P*



GHH[®]*ULTRA-S*



GHH[®]*ULTRA-R*



BONAE-LOCK®L

Splitted design: One or two rubber rings or a number of rubber elements between wheel tyre and wheel body are mainly loaded by compression respectively sheer and compression

Splitted design: A number of rubber pads or two rubber elements are pre-stressed between wheel tyre and wheel body by means of pressure disc respecti-vely wedge ring. The rubber pads / elements are loaded by shear – low radial stiffness of resilient wheel!

EN 45545 Compliance

GHH-BONATRANS is the first resilient wheel producer to comply with EN 45545 protection standard on all components of a resilient wheel.

Czech Republic

BONATRANS GROUP a.s. Revoluční 1234 735 94 Bohumín Czech Republic

India

Bonatrans India Private Limited Plot No. A – 119 Shendra Five Star Industrial Area Shendra MIDC, Aurangabad – 431 154 Maharashtra, India

Germany

Gutehoffnungshütte Radsatz GmbH Gartenstrasse 40 D-46145 Oberhausen Germany

Hong Kong

Bonatrans Asia Limited Rooms 2103–4, 21/F., Wing On Centre 111 Connaught Road, Central Hong Kong

